



**ELECTRIC CHARACTERISTICS**

Nominal voltage	<b>230 Vac</b> (Additional voltage available upon request)
Frequency	<b>50/60 Hz</b>
Regulation	<b>Average</b>
Core type	<b>Toroidal</b>
Input	<b>Symmetric</b>

<b>FINSMT</b>	<b>Rated Power (KVA)</b>	<b>Rated Current (A)</b>	<b>Voltage Variation (%)</b>	<b>Response Time (ms/V)</b>	<b>Output Accuracy (±%)</b>	<b>Dimensions (mm) a x b x h</b>	<b>Weight Kg</b>	<b>Case</b>
FINSMT.30.A1	1	4.3	±30	13	± 1,5	210x385x200	18	1
FINSMT.25.B1	1	4.3	±25	14	± 1,5	210x385x200	20	1
FINSMT.20.B2.5	2 / 2.5	8.7 / 11	±20 / ±15	15 / 18	± 1,5	210x385x200	20	1
FINSMT.10.B3	3	13	±10	25	± 1,5	210x385x200	20	1
FINSMT.30.B2	2	8.7	±30	20	± 0.5	485X500X275	36	2
FINSMT.25.B3	3	13	±25	20	± 0.5	485X500X275	36	2
FINSMT.20.B4	4	17	±20	23	± 0.5	485X500X275	36	2
FINSMT.15.B5	5	22	±15	27	± 0.5	485X500X275	36	2
FINSMT.10.B8	8	35	±10	33	± 0.5	485X500X275	36	2
FINSMT.30.C3	3	13	±30	24	± 0.5	485X500X275	47	2
FINSMT.25.C4	4	17.4	±25	25	± 0.5	485X500X275	47	2
FINSMT.20.C6	6	26	±20	27	± 0.5	485X500X275	47	2
FINSMT.15.C7	7	30	±15	30	± 0.5	485X500X275	47	2
FINSMT.10.C10	10	43	±10	35	± 0.5	485X500X275	47	2
FINSMT.30.D6	6	26	±30	24	± 0.5	485X500X275	60	2
FINSMT.25.D8	8	35	±25	23	± 0.5	485X500X275	60	2
FINSMT.20.D10	10	43	±20	27	± 0.5	485X500X275	60	2
FINSMT.15.D15	15	65	±15	30	± 0.5	485X500X275	60	2
FINSMT.10.D20	20	87	±10	35	± 0.5	485X500X275	60	2
FINSMT.30.E12	12	52	±30	20	± 1	650X450X1000	110	3
FINSMT.25.E15	15	65	±25	26	± 1	650X450X1000	110	3
FINSMT.20.E21	21	91	±20	42	± 1	650X450X1000	110	3
FINSMT.15.E30	30	130	±15	58	± 1	650X450X1000	110	3
FINSMT.10.E40	40	174	±10	64	± 1	650X450X1000	110	3

**CASE 1**

**CASE 2**

**CASE 3**
