

ELECTRIC CHARACTERISTICS

| | |
|-----------------|---|
| Nominal voltage | 400 Vac (480 Vac or additional voltage available upon request) |
| Frequency | 50/60 Hz |
| Regulation | Independent |
| Core type | Square section linear core |
| Input | Symmetric |

| FINSTCY | Rated Power (KVA) | Rated Current (A) | Voltage Variation (%) | Response Time (ms/V) | Output Accuracy (±%) | Dimensions (mm) a x b x h | Weight Kg | Case |
|-----------------|-------------------|-------------------|-----------------------|----------------------|----------------------|---------------------------|-----------|------|
| FINSTCY.30.A48 | 48 | 69 | ±30 | 5 | ± 1 | 1100X650X1800 | 485 | 4 |
| FINSTCY.25.A55 | 55 | 79 | ±25 | 6 | ± 1 | 1100X650X1800 | 485 | 4 |
| FINSTCY.20.A75 | 75 | 108 | ±20 | 6 | ± 1 | 1100X650X1800 | 485 | 4 |
| FINSTCY.15.A110 | 110 | 159 | ±15 | 7 | ± 1 | 1100X650X1800 | 485 | 4 |
| FINSTCY.10.A170 | 170 | 245 | ±10 | 11 | ± 1 | 1100X650X1800 | 560 | 4 |
| FINSTCY.30.B70 | 75 | 109 | ±30 | 10 | ± 1 | 1100X650X1800 | 560 | 4 |
| FINSTCY.25.B90 | 90 | 130 | ±25 | 11 | ± 1 | 1100X650X1800 | 560 | 4 |
| FINSTCY.20.B120 | 125 | 181 | ±20 | 12 | ± 1 | 1100X650X1800 | 560 | 4 |
| FINSTCY.15.B170 | 175 | 254 | ±15 | 14 | ± 1 | 1100X650X1800 | 560 | 4 |
| FINSTCY.10.B260 | 260 | 377 | ±10 | 18 | ± 1 | 1100X650X1800 | 560 | 4 |
| FINSTCY.30.C100 | 100 | 145 | ±30 | 10 | ± 1 | 1100X650X1800 | 625 | 4 |
| FINSTCY.25.C135 | 135 | 196 | ±25 | 11 | ± 1 | 1100X650X1800 | 625 | 4 |
| FINSTCY.20.C175 | 175 | 254 | ±20 | 12 | ± 1 | 1100X650X1800 | 625 | 4 |
| FINSTCY.15.C255 | 255 | 370 | ±15 | 14 | ± 1 | 1100X650X1800 | 625 | 4 |
| FINSTCY.10.C350 | 350 | 507 | ±10 | 18 | ± 1 | 1100X650X1800 | 625 | 4 |
| FINSTCY.30.D140 | 140 | 203 | ±30 | 15 | ± 1 | 1100X650X1800 | 780 | 4 |
| FINSTCY.25.D185 | 185 | 268 | ±25 | 16 | ± 1 | 1100X650X1800 | 780 | 4 |
| FINSTCY.20.D245 | 245 | 355 | ±20 | 17 | ± 1 | 1100X650X1800 | 780 | 4 |
| FINSTCY.15.D345 | 345 | 500 | ±15 | 20 | ± 1 | 1100X650X1800 | 780 | 4 |
| FINSTCY.10.D530 | 530 | 768 | ±10 | 26 | ± 1 | 1100X650X1800 | 780 | 4 |
| FINSTCY.30.E205 | 205 | 297 | ±30 | 11 | ± 1 | 1100X1100X1800 | 1230 | 4 |
| FINSTCY.25.E255 | 255 | 370 | ±25 | 12 | ± 1 | 1100X1100X1800 | 1230 | 4 |
| FINSTCY.20.E345 | 345 | 500 | ±20 | 13 | ± 1 | 1100X1100X1800 | 1230 | 4 |
| FINSTCY.15.E490 | 490 | 710 | ±15 | 15 | ± 1 | 1100X1100X1800 | 1280 | 4 |
| FINSTCY.10.E740 | 740 | 1072 | ±10 | 19 | ± 1 | 1100X1100X1800 | 1280 | 4 |
| FINSTCY.30.F280 | 280 | 406 | ±30 | 16 | ± 1 | 1100X1100X1800 | 1500 | 4 |
| FINSTCY.25.F360 | 360 | 522 | ±25 | 17 | ± 1 | 1100X1100X1800 | 1500 | 4 |
| FINSTCY.20.F490 | 490 | 710 | ±20 | 19 | ± 1 | 1100X1100X1800 | 1530 | 4 |
| FINSTCY.15.F690 | 690 | 1000 | ±15 | 22 | ± 1 | 1100X1100X1800 | 1530 | 4 |
| FINSTCY.10.F960 | 960 | 1391 | ±10 | 27 | ± 1 | 1100X1100X1800 | 1580 | 4 |

| FINSTCY | Rated Power (KVA) | Rated Current (A) | Voltage Variation (%) | Response Time (ms/V) | Output Accuracy (±%) | Dimensions (mm) a x b x h | Weight Kg | Case |
|------------------|--------------------------|--------------------------|------------------------------|-----------------------------|-----------------------------|----------------------------------|------------------|-------------|
| FINSTCY.30.G380 | 380 | 551 | ±30 | 13 | ± 1 | 3 units 1100x1100x1800 | 2750 | 4 (3u) |
| FINSTCY.25.G500 | 500 | 725 | ±25 | 14 | ± 1 | 3 units 1100x1100x1800 | 2750 | 4 (3u) |
| FINSTCY.20.G690 | 690 | 1000 | ±20 | 16 | ± 1 | 3 units 1100x1100x1800 | 2750 | 4 (3u) |
| FINSTCY.15.G1000 | 1000 | 1449 | ±15 | 27 | ± 1 | 3 units 1100x1100x1800 | 2950 | 4 (3u) |
| FINSTCY.10.G1500 | 1500 | 2165 | ±10 | 44 | ± 1 | 3 units 1100x1100x1800 | 2950 | 4 (3u) |
| FINSTCY.30.H520 | 520 | 754 | ±30 | 18 | ± 1 | 3 units 1100x1100x1800 | 3200 | 4 (3u) |
| FINSTCY.25.H690 | 690 | 1000 | ±25 | 20 | ± 1 | 3 units 1100x1100x1800 | 3200 | 4 (3u) |
| FINSTCY.20.H920 | 920 | 1333 | ±20 | 23 | ± 1 | 3 units 1100x1100x1800 | 3350 | 4 (3u) |
| FINSTCY.15.H1300 | 1300 | 1884 | ±15 | 27 | ± 1 | 3 units 1100x1100x1800 | 3450 | 4 (3u) |
| FINSTCY.10.H1900 | 1900 | 2754 | ±10 | 36 | ± 1 | 3 units 1100x1100x1800 | 3450 | 4 (3u) |
| FINSTCY.30.I770 | 770 | 1116 | ±30 | 18 | ± 1 | 3 units 1100x1100x1800 | 4370 | 4 (3u) |
| FINSTCY.25.I1000 | 1000 | 1449 | ±25 | 20 | ± 1 | 3 units 1100x1100x1800 | 4370 | 4 (3u) |
| FINSTCY.20.I1330 | 1330 | 1928 | ±20 | 23 | ± 1 | 3 units 1100x1100x1800 | 4370 | 4 (3u) |
| FINSTCY.15.I1800 | 1800 | 2609 | ±15 | 27 | ± 1 | 3 units 1100x1100x1800 | 4450 | 4 (3u) |
| FINSTCY.10.I2800 | 2800 | 4058 | ±10 | 36 | ± 1 | 3 units 1100x1100x1800 | 4450 | 4 (3u) |
| FINSTCY.30.L1100 | 1100 | 1588 | ±30 | 20 | ± 1 | 3 units 2020x1410x2010 | 6800 | 4 (3u) |
| FINSTCY.25.L1400 | 1400 | 2021 | ±25 | 23 | ± 1 | 3 units 2020x1410x2010 | 6800 | 4 (3u) |
| FINSTCY.20.L1800 | 1800 | 2598 | ±20 | 26 | ± 1 | 3 units 2020x1410x2010 | 7035 | 4 (3u) |
| FINSTCY.15.L2500 | 2500 | 3609 | ±15 | 30 | ± 1 | 3 units 2020x1410x2010 | 7300 | 4 (3u) |
| FINSTCY.10.L4000 | 4000 | 5774 | ±10 | 39 | ± 1 | 3 units 2020x1410x2010 | 7300 | 4 (3u) |

CASE 4
