


ELECTRIC CHARACTERISTICS

Nominal voltage	400 Vac (480 Vac or additional voltage available upon request)
Frequency	50/60 Hz
Regulation	Average
Core type	Toroidal
Input	Symmetric

FINSTT	Rated Power (KVA)	Rated Current (A)	Voltage Variation (%)	Response Time (ms/V)	Output Accuracy (±%)	Dimensions (mm) a x b x h	Weight Kg	Case
FINSTT.30.A3	3	4	±30	13	± 1	600X300X260	45	1
FINSTT.25.A3.5	3.5	4	±25	15	± 1	600X300X260	45	1
FINSTT.20.A6S	5 / 6	7 / 9	±20 / ±15	18 / 21	± 1	600X300X260	45	1
FINSTT.10.A9	9	13	±10	30	± 1	600X300X260	45	1
FINSTT.30.B6	6	9	±30	13	± 1	270X445X480	78	1
FINSTT.25.B6.5	6.5	9.4	25	15	± 1	270X445X480	78	1
FINSTT.20.B12S	9 / 12	13 / 17	±20 / ±15	21	± 1	270X445X480	78	1
FINSTT.10.B17	17	25	±10	30	± 1	270X445X480	78	1
FINSTT.30.C10	10	13	±30	15	± 1	650X450X1000	122	3
FINSTT.25.C13	13	14	±25	16	± 1	650X450X1000	122	3
FINSTT.20.C17	17	22	±20	18	± 1	650X450X1000	122	3
FINSTT.15.C22	22	30	±15	21	± 1	650X450X1000	122	3
FINSTT.10.C31	31	45	±10	21	± 1	650X450X1000	122	3

CASE 1

CASE 3
